

Power-PRO™ IT

Powered Incubator Transport



3800 E. Centre Avenue
Portage, MI 49002 USA
t: 269 329 2100
toll free: 800 327 0770
ems.stryker.com

Standard Features

- Manual back-up release handle
- Automatic high-speed retract
- Battery-powered hydraulic lift system
- Preventative maintenance hour meter
- Battery pack power level indicator
- Color-coded controls
- High visibility powder-coated frame
- Lightweight, rugged aluminum construction
- Lift-capable safety bar
- Scientifically optimized lift bar and control design
- Integrated bumper system
- Retractable head section
- Oversized wheels with sealed caster and wheel bearings
- Built-in pull handle
- X-frame guards
- Power washable
- Tie down brackets
- Compatible with airsled or equivalent configurations
- SMRT power system (12V DC, 120V AC and 240V AC options available)

Optional Features

- Rigid push bars
- Dual wheel locks
- Litter extension
- Head end storage flat
- Base storage net
- SMRT charger mounting bracket
- Power-LOAD compatibility

Compatibility

- Airborne Stackable
- Airborne Side-by-Side
- Dräger Stackable
- Dräger Extended
- No adapter option

Specifications

Model Number 6516

Height¹ (infinite height positioning between lowest and highest position)

Highest Position	41.5 in. (105 cm)
Lowest Position	14 in. (36 cm)

Length

Standard	63 in. (160 cm)
Maximum	81 in. (206 cm)

Width

Width	23 in. (58 cm)
-------	----------------

Weight ²	134 lb (61 kg)
---------------------	----------------

Wheels

Diameter	6 in (15 cm)
Width	2 in (5 cm)

Maximum Weight Capacity³ 700 lb (318 kg)

Minimum Operators Required

Occupied Cot	2
Unoccupied Cot	1

Recommended Fastener System

Power-LOAD	Model 6390
Floor Mount	Model 6370 or 6377
Wall Mount	Model 6371

Recommended Loading Height⁴

Recommended Loading Height ⁴	Up to 36 in (91 cm)
---	---------------------

Warranty

- Two-year parts, and labor
- Two year bumper to bumper or three year bumper to bumper
- One-year soft goods
- Three-year X-frame components
- Three-year limited powertrain
- Lifetime on all welds*

Extended warranties available.

*7-year service life.

¹ Height measured from the top of cot, at the center point, to ground level.

² Cot is weighed with one battery pack, without incubator.

³ 700 lb weight capacity with an unassisted lift capacity of 500 lb (Cot loads over 300 lb (136 kg) may require additional assistance to meet the set cot load height).

⁴ Can accommodate load decks up to 36 in, 91cm. Load height can be set between 26 in and 36 in. (66cm to 91cm)

Stryker reserves the right to change specifications without notice.

In-service video included with each order.

The Power-PRO IT is recognized by Underwriters Laboratory to IEC-60601-1.

The Power-PRO IT is designed to conform to Federal Specification for the Star-of-Life Ambulance KKK-A-1822.

The Power-PRO IT is designed to be compatible with competitive cot fastener systems.

The yellow and black color scheme is a registered trademark of Stryker Corporation.

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: **Power-LOAD, Power-PRO, Stryker**, . All other trademarks are trademarks of their respective owners or holder.

Electrical and Mechanical Safety Certifications



Copyright © 2017 Stryker
Mkt Lit-147-27 Jun 2006 Rev F1
Printed in U.S.A.